



## BEARING DRIVESHAFT, INC.



20 mm x 42 mm x 8 mm skf 16004 bearing

Bearing No. 16004

16004 Bearing 2D drawings and 3D CAD models

Size	42x20x8 mm
Bore Diameter	42 mm
Outer Diameter	20 mm
Width	8 mm
d	20 mm
D	42 mm
B	8 mm
d <sub>1</sub>	27.25 mm
D <sub>2</sub>	37.19 mm
r <sub>1,2</sub> - min.	0.3 mm
d <sub>a</sub> - min.	22 mm
D <sub>a</sub> - max.	40 mm
r <sub>a</sub> - max.	0.3 mm
Basic dynamic load rating - C	7.3 kN
Basic static load rating - C <sub>0</sub>	4 kN
Fatigue load limit - P <sub>u</sub>	0.173 kN
Reference speed	38000 r/min
Limiting speed	24000 r/min
Calculation factor - k <sub>r</sub>	0.02
Calculation factor - f <sub>0</sub>	15
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.052



## BEARING DRIVESHAFT, INC.

Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	20MM Bore; 42MM Outside Diameter; 8MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	16004
Weight / LBS	0.115
Bore	0.787 Inch   20 Millimeter
Outer Race Width	0.315 Inch   8 Millimeter
Outside Diameter	1.654 Inch   42 Millimeter
$d_1$	27.25 mm
$d_a$ min.	22 mm
$D_a$ max.	40 mm
$r_a$ max.	0.3 mm
Basic dynamic load rating C	7.28 kN



## BEARING DRIVESHAFT, INC.

Basic static load rating $C_0$	4.05 kN
Fatigue load limit $P_u$	0.173 kN
Calculation factor $k_r$	0.02
Calculation factor $f_0$	14.9
Mass bearing	0.051 kg