




BEARING DRIVESHAFT, INC.

skf 51214 bearing

Bearing No. 51214



51214 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|---------------------|
| Size | 70x105x27 mm |
| Bore Diameter | 70 mm |
| Outer Diameter | 105 mm |
| Width | 27 mm |
| d | 70 mm |
| D | 105 mm |
| H | 27 mm |
| d1 | 105 mm |
| r1 min. | 1 mm |
| r2 min. | 1 mm |
| D1 | 72 mm |
| da min. | 91 mm |
| Da max. | 84 mm |
| ra max. | 1 mm |
| Weight | 0,79 Kg |
| Basic dynamic load rating (C) | 62,4 kN |
| Basic static load rating (C0) | 160 kN |
| Fatigue load limit (Pu) | 5,85 |
| Reference speed | 2600 r/min |
| Limiting speed | 3600 r/min |
| Category | Thrust Ball Bearing |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.791 |
| Product Group | B00308 |



BEARING DRIVESHAFT, INC.

| | |
|-------------------------------------|--|
| Rolling Element | Ball Bearing |
| Thrust Bearing | Yes |
| Single or Double Direction | Single Direction |
| Banded | No |
| Cage Material | Steel |
| Precision Class | ABEC 1 ISO P0 |
| Component Description | Roller Assembly Plus Raceways |
| Other Features | Single Row |
| Long Description | 70MM Bore 1; 72MM Bore 2; 105MM Outside Diameter; 27MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; ABEC 1 ISO P0 Precision |
| Inch - Metric | Metric |
| Category | Thrust Ball Bearings |
| UNSPSC | 31171507 |
| Harmonized Tariff Code | 8482.10.50.08 |
| Noun | Bearing |
| Keyword String | Ball Thrust |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 51214 |
| Weight / LBS | 1.742 |
| Height | 1.063 Inch 27 Millimeter |
| Overall Height with Aligning Washer | 0 Inch 0 Millimeter |
| Bore 1 | 2.756 Inch 70 Millimeter |
| Outside Diameter | 4.134 Inch 105 Millimeter |
| Bore 2 | 2.835 Inch 72 Millimeter |
| bore diameter: | 70 mm |
| static load capacity: | 160 kN |
| outside diameter: | 105 mm |
| | |



BEARING DRIVESHAFT, INC.

| | |
|---|---------------------------|
| dynamic load capacity: | 62.4 kN |
| overall width: | 27 mm |
| maximum rpm: | 3600 RPM |
| thrust bearing type: | Single-Direction |
| cage material: | Steel |
| outside diameter design: | Straight |
| fillet radius: | 1 mm |
| separable or banded: | Separable |
| series: | 512 |
| precision rating: | ABEC 1 (ISO Class Normal) |
| d_1 | 105 mm |
| D_1 | 72 mm |
| $r_{1,2}$ min. | 1 mm |
| d_a min. | 91 mm |
| D_a max. | 84 mm |
| r_a max. | 1 mm |
| Basic dynamic load rating C | 62.4 kN |
| Basic static load rating C_0 | 160 kN |
| Fatigue load limit P_u | 5.85 kN |
| Minimum load factor A | 0.16 |
| Mass bearing (including seat washer where applicable) | 0.79 kg |